

# Timber Shutters

## Pelmet Measuring

### Pelms - 3 Types Available

#### Inside Mount

Pelmet is fixed into the opening and the headboard is screwed up into the opening. The fascia will sit flush with the front of the opening and will not have returns

#### Outside Mount

Pelmet is fixed on to the outside of the opening; normally above the architrave. The headbox is attached using a 30 x 30mm cleat. Fascia and full length returns are supplied

#### Semi-Reveal Mount

Pelmet is fixed half in the opening and half out of the opening and the headboard is screwed up into the opening. An outside mount fascia and returns are supplied. The returns will stop short of the width of the pelmet and hit the face of the opening. To order: Note "Semi Reveal Mounted Pelmet" in the Special Information field on the order form

### Bi-Fold Pelmet with Track

#### Inside & Reveal Mount

When measuring, please provide the reveal opening dimensions

#### Outside Mount

When measuring, provide the bottom of head to floor dimensions for height and outside panel to panel dimensions for the width; excluding sideboards (normally arch to arch measurement)

COMPONENT	MEASUREMENTS
Head Board	100 x 18mm
Head Mounting Cleat	30 x 30mm
Outside Mount Fascia & Returns	95 x 12mm
Inside Mount Fascia & Returns	65 x 12mm
Sideboards	100 x 18mm
Side Mounting Cleat	33 x 33mm
Bottom Board	100 x 18mm
<b>NOTE: All above are inside Measurements</b>	

#### NOTES:

- Pelms are supplied pre-assembled and maximum single length is 3600mm
- Centre Tilt Rods are offset 7mm for better stacking in the open position
- Standard factory deductions are TOP: 52mm & BOTTOM: 20mm